

AD-A256 412



US Army Corps
Engineers

Hydrologic Engineering Center




12

A Generalized Simulation Model for Reservoir System Analysis

Technical Paper No. 137

March 1992



92 10 14 072

DEFENSE TECHNICAL INFORMATION CENTER



9227122

11
pgs

Papers in this series have resulted from technical activities of the Hydrologic Engineering Center. Versions of some of these have been published in technical journals or in conference proceedings. The purpose of this series is to make the information available for use in the Center's training program and for distribution within the Corps of Engineers

The findings in this report are not to be construed as an official Department of the Army position unless so designated by other authorized documents.

The contents of this report are not to be used for advertising, publication, or promotional purposes. Citation of trade names does not constitute an official endorsement or approval of the use of such commercial products.

A Generalized Simulation Model for Reservoir System Analysis¹

By Richard J. Hayes and Marilyn B. Hurst²

Abstract

The U.S. Army Corps of Engineers has planning and management responsibility for over 500 reservoirs across the United States. Although the primary purpose of most of these projects is flood control, many also include water supply, hydropower or water quality as authorized purposes. A generalized reservoir system simulation model suitable for both planning and real-time operation analysis has been developed by the Hydrologic Engineering Center (HEC).

This paper will overview the general capabilities of the model with emphasis on the features of the current release of HEC-5, Version 7.2, dated March 1991.

Background

The development of computer program HEC-5, "Simulation of Flood Control and Conservation Systems" (USACE, 1982) has been driven by the changing requirements of the Corps of Engineers. As with the other generalized programs of the Hydrologic Engineering Center, the needs of Corps field offices have provided the major determinant for continued program development.

The initial formulation of the program began in 1972, as a single event, multi-reservoir, flood control only model. The goal was to develop a computer program useful for planning and design studies with the anticipated eventual extension to include project operation in real-time. The importance of a generalized flood simulation model was demonstrated almost immediately as HEC-5 made it possible to model the Susquehanna, Potomac, James and Schuylkill River basins to evaluate the impact of Tropical Storm Agnes on various combinations of existing and proposed reservoirs.

In 1974, the model was expanded from single event to multi-event with basic water supply and hydropower analysis capabilities. Average annual flood damage and benefit computations were also added.

The requirement to evaluate pumped-storage hydropower fostered the development of HEC-5's system power and pumped-storage hydropower analysis capability in 1977. These developments coincided with the addition of firm-yield optimization of conservation features (including installed capacity and firm-energy). The usefulness of a generalized hydropower model was proven decidedly with thousands of HEC-5 applications made in support of the National Hydropower Study during 1978 to 1981.

The HEC-5 water quality modeling capability was initiated in 1979 with the addition of the capability to simulate water temperature for a single reservoir. In the following four years the ability to simulate a multi-reservoir system for up to eight water quality constituents was developed and field tested. In support of the Columbia River System Operation Review, a major expansion of the HEC-5 water quality analysis capability is presently underway.

¹ Presented at the ASCE 4th Water Resources Operations Management Workshop, 16-18 March 1992, Mobile, AL.

² Hydraulic Engineer and Computer Programmer, respectively, US Army Corps of Engineers, Water Resources Support Center, Hydrologic Engineering Center, Davis, CA.

In 1980, HEC-5 was modified to transfer data to and from the newly developed HEC Data Storage System, HEC-DSS (USACE, 1990). The development of this link with the Corps rainfall-runoff forecasting program, HEC1F (USACE, 1989), has proven to be significant in advancing the original goal of computer aided real-time water control. Since 1980 a major emphasis of HEC-5 development has been real-time water control.

Program Modernization

The development of HEC-5 from its inception until the early 80's occurred on large mainframe computers. In 1980, HEC acquired a HARRIS mini-computer and a gradual transformation of HEC-5 began. Modernization of the HEC-5 source code began in earnest in 1984 with the primary goal of minimizing the cost of program support, eliminating potential malfunctions, and facilitating the addition of future enhancements.

Major tasks of the modernization process included: (1) conversion of the FORTRAN IV code to FORTRAN-77 specifications; (2) subdivision of 12 large subroutines into 102 smaller modules; (3) redesign of COMMON blocks and subroutine arguments; (4) development of PARAMETER statements; (5) extensive internal documentation; and (6) centralization and simplification of primary program logic. In addition to the code modernization effort, over 90 new test data sets (which test most of the HEC-5 flood control, water supply, and hydropower features) were developed to enhance program quality assurance.

As a continuation of these modernization efforts, HEC-5 was adapted to an HP-9000 computer, an AMDAHL computer and finally in 1987 to a PC. Currently, HEC-5 is being adapted to a variety of UNIX workstations.

Two major benefits of this modernization effort have been noted. First, the adaptation of this very large and rather complex program from mainframe computers to the ubiquitous PC was made possible; and, second, since the retirement of HEC-5 author Bill S. Eichert in February 1989, the HEC staff responsible for HEC-5 have been able to continue maintenance and development.

Model Operation

The basic reservoir system analysis provided by HEC-5 is typically categorized as descriptive simulation. This type of model illustrates the consequence of a set of decisions (operational rules and goals) given a sequence of events. As an example, a descriptive simulation reservoir model shows the effect of a system of reservoirs with specified storage allocations, given downstream channel capacities and a specified series of historical or hypothetical flows.

The results of an HEC-5 simulation are comparable to those obtained with the optimization technique termed "preemptive goal programming", as described by Loganathan and Bhattacharya (1990). For each simulation period, seventeen releases are determined and evaluated for each reservoir.

The normal bias of HEC-5 is to favor flood control operation over conservation operation. The program user however can change the prioritization of release selection to favor hydropower or water supply operation over flood control.

To evaluate flood control, the model determines releases based on the following conditions: (1) channel capacity at the reservoir, (2) channel capacity at downstream locations, and (3) rate-of-change rising. The smallest of these releases is selected as the flood control release. To evaluate potential conservation releases, the following are determined: (1) water supply at the reservoir, (2) water supply for downstream locations, (3) at-site power, and (4) system power. The largest of these is selected as the conservation release.

A release check is made during each simulation period to insure that the tentatively selected release is as least as large as the computed emergency release (if any) or rate-of-change falling. As a final check on operation, the tentative release is limited by outlet capacity and availability of water.

Data Requirements

The basic input requirements consist of three types of data: (1) **Physical data** including: storage-discharge capacity curves, linkages defining the system structure, hydrologic routing criteria; (2) **Operational data** including: allocation of reservoir storage volumes to project purpose (rule curves), forecast ability, maximum allowable flow goals (channel capacities), minimum flow goals; and (3) **Hydrologic time-series data** consisting primarily of flow data.

Program Capabilities

HEC-5 is capable of simulating the operation of simple or complex systems of reservoirs of almost any configuration. Analysis may be made in a planning mode, or when coupled with HEC runoff forecast programs through the data storage system, analysis may be made in a real-time mode.

Hydrologic time-series data may be specified in a variety of simulation time intervals including minutes, hours, days, weeks, 10-daily, half-months and months. Flow data may be specified as end-of-period or period-average. Analysis may be made for single events, multiple events or period-of-record analysis. General capabilities are summarized in Table 1.

Table 1 HEC-5 General Capabilities

- English or SI Units
- Up to 20 Reservoirs
- Up to 40 Control Points
- 7 Hydrologic Routing Methods
- Linked to HEC-DSS Data Storage System
- Simulation Intervals from Minutes to a Month
- Single Event or Period-of-Record Simulation
- Flood Control, Water Supply, Hydropower and Water Quality Analysis

Accession For	
NTIS CRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By	
Distribution /	
Availability	
Dist	Avail
A-1	

Flood Control

During a flood event, the model operates the reservoirs to minimize flood damages by limiting releases such that the routed reservoir releases when combined with local runoff will not exceed downstream channel capacities. To do this, the model stores inflows in the flood storage pool. When downstream local flows decrease, the model will increase reservoir releases to return the flood storage pool to an empty condition as rapidly as possible.

For a system of flood control reservoirs, releases are determined to balance the flood control storage among the reservoirs based on the specified storage "levels". These levels may be used to prioritize flood control storage usage among system reservoirs to reflect the probability of filling, or some other "balancing" criteria.

For planning applications, realistic flood control simulation is achieved through the use of a limit on forecast ability both in time and precision of flow forecast. Economic evaluation of flood damage computations may be made for historic floods or on an average annual basis.

For real-time water control applications, HEC-5 is used in conjunction with the HEC runoff forecasting program HEC1F and other programs of the HEC water control software system. Water control operators can efficiently evaluate HEC-5 real-time simulations via graphical output from the HEC-DSS graphics program DISPLAY. Flood control features are summarized in Table 2.

Table 2 HEC-5 Flood Control Features

- Balanced Pool System Operation
- Gated Spillway Simulation
- Rate-of-Change Constraints
- Pre-Release Options
- 7 Variable Channel Capacity Options
- Forecast Limits and Contingency Factors
- Flood Damage Economic Computations

Water Supply

During a low-flow sequence, reservoir releases (combined with downstream local flows) are made to satisfy downstream instream and diversion water supply demands. When downstream local flows are capable of satisfying these demands, the releases are reduced until the conservation pool is filled or until water supply requirements again require additional releases.

Reservoir systems are operated for water supply goals in a balanced pool mode utilizing conservation zone storage levels in the same way as flood control operation (e.g. reservoirs with higher levels release first to meet downstream demands).

HEC-5 also provides the ability to optimize reservoir storage, reservoir yield, diversions and downstream flow goals on a firm-yield basis. Water supply features are summarized in Table 3.

Table 3 HEC-5 Water Supply Features

- Variable Instream Flow Goals
- 7 Diversion Types
- Evaporative Losses/Gains
- Firm-Yield Optimization of Storage, Yield, Diversions, Downstream Goals

Hydropower

HEC-5 hydropower simulation capabilities include analysis of run-of-river, peaking, pumped storage and system power. To simulate hydropower operation, reservoir releases are determined to meet power production goals which may vary on a monthly, daily, or hourly basis. In addition, at-site and system power requirements may be specified as a function of storage.

HEC-5 also includes the ability to optimize installed capacity and firm energy on a firm-yield basis. Hydropower features are summarized in Table 4.

Table 4 HEC-5 Hydropower Features

- Peaking Power
- Run-of-River Generation
- System Power Operation
- Leakage Specification
- Penstock capacity and losses
- Efficiency a function of Storage or Head
- Capacity as a function of Storage, Head or Release
- Monthly, Daily and Hourly Power Demands
- Firm-Yield Optimization of Energy and Capacity

Water Quality

Program HEC-5Q (USACE, 1986) is a specialized edition of HEC-5 which in addition to flood control, water supply, and hydropower also includes water quality analysis. The capabilities of this water quality edition are summarized in Table 5.

Table 5 HEC-5Q Water Quality Features

- Operation of Multi-Level Discharge Ports
- Downstream Temperature Goals
- Downstream Dissolved Oxygen Goals
- Up to 3 Conservative Constituents
- Up to 3 Non-Conservative Constituents

Program Configurations and Availability

Prior to 1987, HEC-5 was available to Corps offices as a mainframe executable program. FORTRAN source code was available for non-Corps offices. In 1987 the first PC edition of HEC-5 was released. This edition was developed for INTEL 8088 DOS based PCs (e.g., IBM-XT). Due to the limited memory addressing inherent with 8088 systems, this edition relied upon an extensive overlay structure and a reduction in both temporal and spatial capabilities. This overlaid edition was released to both Corps and non-Corps offices.

In 1988, an extended memory edition was developed utilizing licensed extended memory management software rather than an overlay scheme. The extended memory edition provided mainframe capabilities and a significant increase in execution speed. However, due to the licensing requirements these editions were released only to Corps offices.

The current release of HEC-5 is Version 7.2, dated March 1991. Three PC DOS configurations include: (1) an overlaid edition suitable for XTs with 640kb memory, math coprocessor, and a hard disk; (2) an extended memory edition which suitable for a 386 PC with math coprocessor, hard disk and 2-4 Mb of memory; and (3) an extended memory edition of HEC-5Q suitable for a 386 PC with math coprocessor, hard disk and 2-8 Mb of memory. HEC software including HEC-5 are available from the National Technical Information Service (NTIS) as well as software vendors.

References

Loganathan, G.V. and Bhattacharya, D., 1990, "Goal-Programming Techniques for Optimal Reservoir Operations", *Journal of Water Resources Planning and Management*, Vol. 116, No. 6, 820-838.

US Army Corps of Engineers, April 1982, HEC-5, Simulation of Flood Control and Conservation Systems, User's Manual (without Exhibit 8), CPD-5A, Hydrologic Engineering Center, Davis, CA.

US Army Corps of Engineers, September 1986, HEC-5, Simulation of Flood Control and Conservation Systems, Appendix on Water Quality Analysis, CPD-5Q, Hydrologic Engineering Center, Davis, CA.

US Army Corps of Engineers, November 1989, Water Control Software, Forecast and Operations, Hydrologic Engineering Center, Davis, CA.

US Army Corps of Engineers, December 1990, HECDSS, User's Guide and Utility Program Manuals, CPD-45, Hydrologic Engineering Center, Davis, CA.

TECHNICAL PAPER SERIES

(\$2 per paper)

TP-1	Use of Interrelated Records to Simulate Streamflow	TP-37	Downstream Effects of the Levee Overtopping at Wilkes-Barre, PA, During Tropical Storm Agnes
TP-2	Optimization Techniques for Hydrologic Engineering	TP-38	Water Quality Evaluation of Aquatic Systems
TP-3	Methods of Determination of Safe Yield and Compensation Water from Storage Reservoirs	TP-39	A Method for Analyzing Effects of Dam Failures in Design Studies
TP-4	Functional Evaluation of a Water Resources System	TP-40	Storm Drainage and Urban Region Flood Control Planning
TP-5	Streamflow Synthesis for Ungaged Rivers	TP-41	HEC-5C, A Simulation Model for System Formulation and Evaluation
TP-6	Simulation of Daily Streamflow	TP-42	Optimal Sizing of Urban Flood Control Systems
TP-7	Pilot Study for Storage Requirements for Low Flow Augmentation	TP-43	Hydrologic and Economic Simulation of Flood Control Aspects of Water Resources Systems
TP-8	Worth of Streamflow Data for Project Design - A Pilot Study	TP-44	Sizing Flood Control Reservoir Systems by Systems Analysis
TP-9	Economic Evaluation of Reservoir System Accomplishments	TP-45	Techniques for Real-Time Operation of Flood Control Reservoirs in the Merrimack River Basin
TP-10	Hydrologic Simulation in Water-Yield Analysis	TP-46	Spatial Data Analysis of Nonstructural Measures
TP-11	Survey of Programs for Water Surface Profiles	TP-47	Comprehensive Flood Plain Studies Using Spatial Data Management Techniques
TP-12	Hypothetical Flood Computation for a Stream System	TP-48	Direct Runoff Hydrograph Parameters Versus Urbanization
TP-13	Maximum Utilization of Scarce Data in Hydrologic Design	TP-49	Experience of HEC in Disseminating Information on Hydrological Models
TP-14	Techniques for Evaluating Long-Term Reservoir Yields	TP-50	Effects of Dam Removal: An Approach to Sedimentation
TP-15	Hydrostatistics - Principles of Application	TP-51	Design of Flood Control Improvements by Systems Analysis: A Case Study
TP-16	A Hydrologic Water Resource System Modeling Techniques	TP-52	Potential Use of Digital Computer Ground Water Models
TP-17	Hydrologic Engineering Techniques for Regional Water Resources Planning	TP-53	Development of Generalized Free Surface Flow Models Using Finite Element Techniques
TP-18	Estimating Monthly Streamflows Within a Region	TP-54	Adjustment of Peak Discharge Rates for Urbanization
TP-19	Suspended Sediment Discharge in Streams	TP-55	The Development and Servicing of Spatial Data Management Techniques in the Corps of Engineers
TP-20	Computer Determination of Flow Through Bridges	TP-56	Experiences of the Hydrologic Engineering Center in Maintaining Widely Used Hydrologic and Water Resource Computer Models
TP-21	An Approach to Reservoir Temperature Analysis	TP-57	Flood Damage Assessments Using Spatial Data Management Techniques
TP-22	A Finite Difference Method for Analyzing Liquid Flow in Variably Saturated Porous Media	TP-58	A Model for Evaluating Runoff-Quality in Metropolitan Master Planning
TP-23	Uses of Simulation in River Basin Planning	TP-59	Testing of Several Runoff Models on an Urban Watershed
TP-24	Hydroelectric Power Analysis in Reservoir Systems	TP-60	Operational Simulation of a Reservoir System with Pumped Storage
TP-25	Status of Water Resource Systems Analysis	TP-61	Technical Factors in Small Hydropower Planning
TP-26	System Relationships for Panama Canal Water Supply	TP-62	Flood Hydrograph and Peak Flow Frequency Analysis
TP-27	System Analysis of the Panama Canal Water Supply	TP-63	HEC Contribution to Reservoir System Operation
TP-28	Digital Simulation of an Existing Water Resources System	TP-64	Determining Peak-Discharge Frequencies in an Urbanizing Watershed: A Case Study
TP-29	Computer Applications in Continuing Education	TP-65	Feasibility Analysis in Small Hydropower Planning
TP-30	Drought Severity and Water Supply Dependability	TP-66	Reservoir Storage Determination by Computer Simulation of Flood Control and Conservation Systems
TP-31	Development of System Operation Rules for an Existing System by Simulation	TP-67	Hydrologic Land Use Classification Using LANDUSE
TP-32	Alternative Approaches to Water Resource System Simulation	TP-68	Interactive Nonstructural Flood-Control Planning
TP-33	System Simulation for Integrated Use of Hydroelectric and Thermal Power Generation	TP-69	Critical Water Surface by Minimum Specific Energy Using the Parabolic Method
TP-34	Optimizing Flood Control Allocation for a Multipurpose Reservoir	TP-70	Corps of Engineers Experience with Automatic Calibration of a Precipitation-Runoff Model
TP-35	Computer Models for Rainfall-Runoff and River Hydraulic Analysis		
TP-36	Evaluation of Drought Effects at Lake Atitlan		

- TP-71 Determination of Land Use from Satellite Imagery for Input to Hydrologic Models
- TP-72 Application of the Finite Element Method to Vertically Stratified Hydrodynamic Flow and Water Quality
- TP-73 Flood Mitigation Planning Using HEC-SAM
- TP-74 Hydrographs by Single Linear Reservoir Model
- TP-75 HEC Activities in Reservoir Analysis
- TP-76 Institutional Support of Water Resource Models
- TP-77 Investigation of Soil Conservation Service Urban Hydrology Techniques
- TP-78 Potential for Increasing the Output of Existing Hydroelectric Plants
- TP-79 Potential Energy and Capacity Gains from Flood Control Storage Reallocation at Existing U. S. Hydropower Reservoirs
- TP-80 Use of Non-Sequential Techniques in the Analysis of Power Potential at Storage Projects
- TP-81 Data Management Systems for Water Resources Planning
- TP-82 The New HEC-1 Flood Hydrograph Package
- TP-83 River and Reservoir Systems Water Quality Modeling Capability
- TP-84 Generalized Real-Time Flood Control System Model
- TP-85 Operation Policy Analysis: Sam Rayburn Reservoir
- TP-86 Training the Practitioner: The Hydrologic Engineering Center Program
- TP-87 Documentation Needs for Water Resources Models
- TP-88 Reservoir System Regulation for Water Quality Control
- TP-89 A Software System to Aid in Making Real-Time Water Control Decisions
- TP-90 Calibration, Verification and Application of a Two-Dimensional Flow Model
- TP-91 HEC Software Development and Support
- TP-92 Hydrologic Engineering Center Planning Models
- TP-93 Flood Routing Through a Flat, Complex Flood Plain Using a One-Dimensional Unsteady Flow Comput Program
- TP-94 Dredged-Material Disposal Management Model
- TP-95 Infiltration and Soil Moisture Redistribution in HEC-1
- TP-96 The Hydrologic Engineering Center Experience in Nonstructural Planning
- TP-97 Prediction of the Effects of a Flood Control Project on a Meandering Stream
- TP-98 Evolution in Computer Programs Causes Evolution in Training Needs: The Hydrologic Engineering Center Experience
- TP-99 Reservoir System Analysis for Water Quality
- TP-100 Probable Maximum Flood Estimation - Eastern United States
- TP-101 Use of Computer Program HEC-5 for Water Supply Analysis
- TP-102 Role of Calibration in the Application of HEC-6
- TP-103 Engineering and Economic Considerations in Formulating
- TP-104 Modeling Water Resources Systems for Water Quality
- TP-105 Use of a Two-Dimensional Flow Model to Quantify Aquatic Habitat
- TP-106 Flood-Runoff Forecasting with HEC-1F
- TP-107 Dredged-Material Disposal System Capacity Expansion
- TP-108 Role of Small Computers in Two-Dimensional Flow Modeling
- TP-109 One-Dimensional Model For Mud Flows
- TP-110 Subdivision Froude Number
- TP-111 HEC-5Q: System Water Quality Modeling
- TP-112 New Developments in HEC Programs for Flood Control
- TP-113 Modeling and Managing Water Resource Systems for Water Quality
- TP-114 Accuracy of Computed Water Surface Profiles - Executive Summary
- TP-115 Application of Spatial-Data Management Techniques in Corps Planning
- TP-116 The HEC's Activities in Watershed Modeling
- TP-117 HEC-1 and HEC-2 Applications on the MicroComputer
- TP-118 Real-Time Snow Simulation Model for the Monongahela River Basin
- TP-119 Multi-Purpose, Multi-Reservoir Simulation on a PC
- TP-120 Technology Transfer of Corps' Hydrologic Models
- TP-121 Development, Calibration and Application of Runoff Forecasting Models for the Allegheny River Basin
- TP-122 The Estimation of Rainfall for Flood Forecasting Using Radar and Rain Gage Data
- TP-123 Developing and Managing a Comprehensive Reservoir Analysis Model
- TP-124 Review of the U.S. Army Corps of Engineering Involvement With Alluvial Fan Flooding Problems
- TP-125 An Integrated Software Package for Flood Damage Analysis
- TP-126 The Value and Depreciation of Existing Facilities: The Case of Reservoirs
- TP-127 Floodplain-Management Plan Enumeration
- TP-128 Two-Dimensional Floodplain Modeling
- TP-129 Status and New Capabilities of Computer Program HEC-6: "Scour and Deposition in Rivers and Reservoirs"
- TP-130 Estimating Sediment Delivery and Yield on Alluvial Fans
- TP-131 Hydrologic Aspects of Flood Warning - Preparedness Programs
- TP-132 Twenty-five Years of Developing, Distributing, and Supporting Hydrologic Engineering Computer Programs
- TP-133 Predicting Deposition Patterns in Small Basins
- TP-134 Annual Extreme Lake Elevations by Total Probability Theorem
- TP-135 A Muskingum-Cunge Channel Flow Routing Method for Drainage Networks
- TP-136 Prescriptive Reservoir System Analysis Model - Missouri River System Application
- TP-137 A Generalized Simulation Model for Reservoir System Analysis

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

1a. REPORT SECURITY CLASSIFICATION Unclassified			1b. RESTRICTIVE MARKINGS		
2a. SECURITY CLASSIFICATION AUTHORITY			3. DISTRIBUTION/AVAILABILITY OF REPORT Unlimited		
2b. DECLASSIFICATION/DOWNGRADING SCHEDULE					
4. PERFORMING ORGANIZATION REPORT NUMBER(S) Technical Paper No. 137			5. MONITORING ORGANIZATION REPORT NUMBER(S)		
6a. NAME OF PERFORMING ORGANIZATION US Army Corps of Engineers Hydrologic Engineering Center		6b. OFFICE SYMBOL (if applicable) CEWRC-HEC	7a. NAME OF MONITORING ORGANIZATION		
6c. ADDRESS (City, State, and ZIP Code) 609 Second Street Davis, California 95616			7b. ADDRESS (City, State, and ZIP Code)		
8a. NAME OF FUNDING/SPONSORING ORGANIZATION		8b. OFFICE SYMBOL (if applicable)	9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER		
8c. ADDRESS (City, State, and ZIP Code)			10. SOURCE OF FUNDING NUMBERS		
			PROGRAM ELEMENT NO.	PROJECT NO.	TASK NO.
			WORK UNIT ACCESSION NO.		
11. TITLE (Include Security Classification) A Generalized Simulation Model for Reservoir System Analysis					
12. PERSONAL AUTHOR(S) Richard J. Hayes and Marilyn B. Hurst					
13a. TYPE OF REPORT Technical Paper		13b. TIME COVERED FROM _____ TO _____		14. DATE OF REPORT (Year, Month, Day) March 1992	
15. PAGE COUNT 6					
16. SUPPLEMENTARY NOTATION					
17. COSATI CODES			18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number)		
FIELD	GROUP	SUB-GROUP	Computer Programs; Simulation; Reservoirs; Flood Control; Reservoir Yield; Hydroelectric Power; Water Supply; Water Quality		
19. ABSTRACT (Continue on reverse if necessary and identify by block number) This paper overviews the general features of computer program "HEC-5, Simulation of Flood Control and Conservation Systems," with emphasis on the capabilities of the most recent release of HEC-5, Version 7.2, dated March 1991. HEC-5 can simulate the essential features and operation goals and constraints of simple or complex systems with simulation intervals ranging from minutes to one month. Single event flood analysis and period of record conservation analysis may be accomplished with the model. Flood control analysis includes balanced system operation for downstream damage centers with consideration of forecasted local flows and hydrologic routing. In addition, induced surcharge operation based on spillway gate regulation schedules can be simulated. Hydropower analysis may include run-of-river, peaking, and pumped storage plants as well as system power operation. Water supply simulation can include reservoir and downstream flow requirements in addition to diversions and return flows. Water Quality analysis can include simulation of temperature, dissolved oxygen, up to three conservative and up to three nonconservative constituents.					
20. DISTRIBUTION/AVAILABILITY OF ABSTRACT <input checked="" type="checkbox"/> UNCLASSIFIED/UNLIMITED <input type="checkbox"/> SAME AS RPT. <input type="checkbox"/> DTIC USERS			21. ABSTRACT SECURITY CLASSIFICATION		
22a. NAME OF RESPONSIBLE INDIVIDUAL Darryl W. Davis, Director			22b. TELEPHONE (Include Area Code) 916 756-1104		22c. OFFICE SYMBOL CEWRC-HEC